



01 SPECIFICATIONS

E100 51.2V 5.12kWh		Voltage	
Model	E100	Nominal	51.2 V
Battery type	LiFePO ₄	Float charge	54.5 V
Battery capacity	100 Ah	Absorption charge	55.5 V
Power capacity	5.12 kWh	Cut-off	48.0 V
Current			
Max continuous charge / discharge current		100 A / 100 A	
Peak current (1sec)		110A / 150 A	
Weight and Dimensions		Temperature	
Dimensions [D x W x H, mm] Rack mounted	480 mm x 482 mm x 133 mm	Charging	0 – 45 °C
Battery weight	45 kg	Discharging	-10 – 45 °C
Other			
Enclosure protection		IP20	
Access interface		CAN Bus / RS485	
Compatible inverters		All leading inverter brands	
Storage conditions		15–30 °C at Min 50% SoC (charge every 6 months)	
Warranted cycles		6000 cycles At 80% DoD	
Warranted calendar life		10 Years	





02 BUILT FOR YOUR HOME — AND BUILT TO LAST.

Smart 16-Cell Design:

Delivers the ideal voltage range for most home and small-business inverters.

Safe LiFePO4 Technology:

One of the safest and most reliable battery types for long-term energy storage.

Universal Compatibility: Works seamlessly with a wide range of inverter brands using CAN or RS485 communication.

Trusted PACE BMS:

An industry-proven Battery Management System that ensures safety and performance.

Easy Monitoring:

A built-in LCD screen lets you view battery performance and settings at a glance.

African-Tough:

Designed to handle high temperatures, humidity, and altitude — perfect for local conditions.

03 KEY FEATURES

- Thin Rack Mount Profile (3U Profile)
- 1C Continuous Discharge, Peaking at 1.5C
- No Depth of Discharge (DoD) enforcement. 100% usage of the battery is both warranted and permitted
- Utilises cells that pass GB/T 36276 tests; this battery has been built high quality cells
- Rated for over 18 MWh of warranted throughput over 10 years
- Maintains support with a number of 3rd party trusted devices including SolarAssistant, AXPI and ESP-BMS

The E100 will be backwards compatible, allowing hassle free expansion of R100 and B100 sites.

Enquiries email: enquiries@revov.co.za
Enquiries: 010 035 6061
WhatsApp: +27 (0)73 159 5938

Technical service desk: 010 035 0680
Technical service email: support@revov.co.za
Technical WhatsApp: +27 (0)69 654 7539

Unit 1, Cranberry Street Industrial Park 1486 Cranberry Street, Honeydew, Roodepoort, 2040