

ATTESTATION OF CONFORMITY

Issued to: Dyness Digital Energy Technology Co., LTD.
Building 1&2, 7th–8th Floors, Building 3, No. 56-58 Nanhu Road, Chengnan
Subdistrict, Wuzhong District, Suzhou City, Jiangsu Province, P.R.China

For the product: Rechargeable Li-ion Battery System

Trade name: **DYNESS**

Type/Model: DH200F-C260P125-S4, DH200F-C260P125-S0,
DH200F-C260P124-S4, DH200F-C260P124-S0

Ratings: See model list

Manufactured by: Dyness Digital Energy Technology Co., LTD.
Building 1&2, 7th–8th Floors, Building 3, No. 56-58 Nanhu Road, Chengnan
Subdistrict, Wuzhong District, Suzhou City, Jiangsu Province, P.R.China

Subject: Complete evaluation of electrical system of the appliances

Requirements: EN IEC 61000-6-2:2019
EN IEC 61000-6-4:2019

This Attestation is granted on account of an examination by DEKRA, the results of which are laid down in a test file / test report no. 6256515.50

This Attestation implies that the examined types are in accordance with the standards designated under the Electromagnetic compatibility directive 2014/30/EU.

The examination has been carried out on one single specimen or several specimens of the product, submitted by the manufacturer. The Attestation does not include an assessment of the manufacturer's production. Conformity of this production with the specimen tested by DEKRA is not the responsibility of DEKRA.

This document does not authorize the use of any DEKRA approved mark.

Arnhem, 22 June 2026

Number: 6256515.01AOC

DEKRA Testing and Certification (Shanghai) Ltd.



Jeuli Zhou
Certification Manager

© Integral publication of this attestation and adjoining reports is allowed

Page 1 of 2

Annex

Document no. : 6256515.01AOC

Model	DH200F- C260P124-S0	DH200F- C260P124-S4	DH200F- C260P125-S0	DH200F- C260P125-S4
Battery Parameter:				
Battery Type	LiFePO ₄			
Battery Capacity (Ah)	314			
PACK Configuration	1P20S*13			
Rated Current (A)	157			
Max. Current (A)	180			
Battery Voltage Range (Vdc)	754 ~ 936			
System Nominal Capacity (kWh)	261			
AC Grid Parameter:				
Rated Input/Output Power (kW)	250 / 124.9	250 / 124.9	250 / 125	250 / 125
Max. Input / Output Current (A)	361 / 200			
Normal AC Voltage (Vac)	3P4L+PE, 400			
Frequency (Hz)	50 / 60			
Power Factor	≥ 0.99			
AC Load Parameter:				
Rated Power (kW)	125			
Normal AC Voltage (Vac)	3P4L+PE, 400			
Frequency (Hz)	50 / 60			
Max. AC Current (A)	200			
PV Parameter:				
Max. Input Power (kW)	---	63 * 4	---	63 * 4
Max. Input Current (A)	---	160 * 4	---	160 * 4
Short-Circuit Current (A)	---	240 * 4	---	240 * 4
Max. Input Voltage (Vdc)	---	720	---	720
Input Voltage Range (Vdc)	---	200 - 720	---	200 - 720

End